

# 16AWG/4C Stranded Riser (CMR) Direct Burial Audio Cable

## Cable Detail



## Approval



## Description

- 16/4 Stranded CMR/CL3R Direct Burial Sound Audio Cable

## Applicable Standards

- For Communication and Signal Control Systems
- 4 Oxygen Free Bare Copper Conductors in an Overall Jacket

## Physical Characteristics

Conductor	Oxygen Free B.C.
Number of Conductor	4
AWG	16
Stranding	65
Diameter	0.0063 (inches)
Insulation Material	PVC
Diameter	0.0827 (inches)
Nominal Wall	0.0098 (inches)
Jacket Material	FR-PVC
Overall Diameter	0.2559 (inches)
Nominal Thickness	0.02165 (inches)
Paper Tape	YES
Rip Cord	YES
Conductor Resistance	15.8 (ohms/1000m)
Voltage	300 (volts)
Nominal Weight	28 (pounds)

## Colors

- Insulation Color  
Black / Red / White / Green
- Jacket Color  
Black

## Part Number

AC1604OSPBK4-500

## Package

500FT / REELEX II

## Cable Marking

AUDIO CABLE 4 COND 16 AWG HI-STRAND OXYGEN FREE COPPER CMR/CL3R DIRECT BURIAL AUDIO CABLE SUN RES EXXXXXX C(ETL)US \*\*\*FT